



AISLAMIENTO Y ESTANQUEIDAD ERICA SL
C/ Marruecos 159-165 08019 BARCELONA Spain
Tel +34 932 663 649 erica@erica.es www.erica.es

CERTIFICADO DE CONFORMIDAD EN 10204 2.2

Nº Cert.: **327 / 23**

CLIENTE: **C008525**

JC FABRICA DE VALVULAS S.A.U.

AISLAMIENTO Y ESTANQUEIDAD ERICA, S.L.

CERTIFICA

QUE EL MATERIAL SUMINISTRADO CON EL ALBARÁN Nº **2308061** DE FECHA **08/09/2023**
CUMPLE LAS DIMENSIONES Y CALIDAD REQUERIDAS SEGÚN LOS DATOS TÉCNICOS ADJUNTOS

Nº PEDIDOS: **JCB232988**

CONCEPTOS

- **10,00 U** ESPIROMETALICA TIPO R INOX316L/GRAFITO Ø144.5X131.8X3.2MM
- **6,00 U** ESPIROMETALICA TIPO R INOX316L/GRAFITO Ø74.9X65.1X4.5MM

Dpto. de Calidad:

15 de septiembre de 2023

INSPECTION CERTIFICATE

Conform to DIN 50 049/EN 10204 3.1

CUSTOMER INDEEL S.A.

Attention to *INDEEL QC*

CUSTOMER ORDER NUMBER : 19/78

CUSTOMER ORDER DATE : 03/05/2019

OUR ORDER CONFIRMATION: 14333

PRODUCT P/FF S

SPECIFICATION N. 304/19

ART. CODE 02V0000109

CUSTOMER SPECIFICATION N.

GRADE FREE FLOW

CUSTOMER CODE N.

BASE MATERIAL

WEIGHT KG 400,0000

LOT. N. 19-1904

COMPOSITION BY WEIGHT % & FILLER DESCRIPTION

100% VIRGIN PTFE

Property	Measuring Method	Units	Test Results	Specification
Specific gravity	ASTM D4894	g/cm ³	2,15	2,16+/-0,02
Tensile strength CD	ASTM D4894	MPa	35,0	min.27
Elongation CD	ASTM D4894	%	325,4	min.280
Hardness - Shore D	ISO 868		D/1:55	54-56
Bulk density	ASTM D4894	g/l	660	700+/-50
Diametric shrinkage	INTERN	%	2,6	2,6+/-0,2

OTHER SPECIFICATIONS:

OTHER:

Q.C. PROCESSING CONDITION:

PREFORM PRESSURE : 300 Kg/cm²

Date 17/05/2019

MAXIMUM SINTERING TEMPERATURE : 375°C

SIZE OF TEST BILLET : 57mm X 70mm

Signature Simone Contaboni

All these data are believed to be accurate and reliable. This inspection certificate does not exempt the Customer from effecting his own quality control in check-in.

